


COMPANY PROFILE

VIME has had a long-standing commitment to producing quality winches throughout its range. Year after year VIME winches have been at the forefront of technology and unequalled performance. Nowadays more European and world industries rely on VIME winches for good performance and uncompromising quality they can offer.

Some operators prefer the heavy duty solid pulling power of a Worm Gear Winch. VIME has what they need from 2,2 to 30 tons capacities. Built with the highest quality our Worm Gear Winches have been the "Choice of Professionals" for over 40 years.

Other operators prefer the fast pay out and compact overall dimensions of a Planetary Gear Winch. VIME has what they need from 3,6 to 20 tons capacities. Built with the highest quality our Planetary Gear Winches claim a reliable brake who offer a smooth control of load.



SMART AND RELIABLE SOLUTIONS



Your needs guide our choices



V.I.M.E. srl Via Gramsci, 15 40050 Furolo Bologna Italy Tel. +39 051 861362 Fax +39 051 861961
 E-mail: info@vimeindustrial.com / Web site: www.vimeindustrial.it - www.vimeindustrial.com


EPH FN PLANETARY WINCHES

Model EPH FN are hydraulic planetary winches. Designed for extend life and give best safe duty. These winches are built according with higher safety standards in compliance with Directive Machinery 2006/42/CE Harmonized EN 14492-1. The high efficiency planetary gear train assure fast payout and rewind winching operational and the innovative brake system, make these winches reliable and great for industrial applications.




CE
EN 14492-1

EPH 3600FN




PULLING CAPACITY	3.600 Kgs	[8.000 Lbs]
WORKING PRESSURE	160 Bar	[2,320 Psi]
WIRE ROPE DIA.	10 mm	
MAX. ROPE CAPACITY	33 Mt	[108,3 Ft]
MAX. SPEED LINE	14,8 Mt/Min	[48,6 Ft/Min]
MAX. OIL SUPPLY	60 Lt/Min	[15,85 GPM]

EPH/L 3600FN



PULLING CAPACITY	3.600 Kgs	[8.000 Lbs]
WORKING PRESSURE	160 Bar	[2,320 Psi]
WIRE ROPE DIA.	10 mm	
MAX. ROPE CAPACITY	43 Mt	[141,1 Ft]
MAX. SPEED LINE	14,8 Mt/Min	[48,6 Ft/Min]
MAX. OIL SUPPLY	60 Lt./Min.	[15,85 GPM]

EPH 4500FN



PULLING CAPACITY	4.500 Kgs	[10.000 Lbs]
WORKING PRESSURE	150 Bar	[2,176 Psi]
WIRE ROPE DIA.	11 mm	
MAX. ROPE CAPACITY	40 Mt	[131,2 Ft]
MAX. SPEED LINE	11,7 Mt/Min	[38,4 Ft/Min]
MAX. OIL SUPPLY	60 Lt/Min	[15,85 GPM]

FEATURES

- COMPACT**
Hardened steel single stage planetary gear train
- FAST WINCHING SPEED**
Fast payout and rewind
- VERSATILE MOUNTING**
Designed for either foot or side mounting
- LIGHT AND STRONG**
Body manufactured from hardened, special aluminium castings reduced weight and increased strength
Powder coat finished
- MULTI-DISC PRESSURE RELEASED BRAKE**
Gives a reliable and effective full brake capacity
- DRUM SIZE AVAILABLE**
Standard: 200 mm (7.9 inch) EPH 3600FN
252 mm (9.9 inch) EPH 4500FN - EPH 5200FN
EPH 6200FN - EPH 6700FN
Long: 252 mm (9.9 inch) EPH/L 3600 FN
- TOTALLY OIL COOLED**
Gears and brake in oil bath for best performance, quiet operation and extended component life


ACCESSORIES :

- Zinc plated Heavy-duty roller fairlead
- Zinc plated Cable tensioner
- Air clutch shifter - drum free spooling




CE
EN 14492-1

EPH 5200FN




PULLING CAPACITY	5.200 Kgs	[11.460 Lbs]
WORKING PRESSURE	130 Bar	[1,885 Psi]
WIRE ROPE DIA.	11 mm	
MAX. ROPE CAPACITY	54 Mt	[177,2 Ft]
MAX. SPEED LINE	8,6 Mt/Min	[28,2 Ft]
MAX. OIL SUPPLY	60 Lt/Min	[15,85 GPM]

EPH 6200FN



PULLING CAPACITY	6.200 Kgs	[13.650 Lbs]
WORKING PRESSURE	155 Bar	[2,248 Psi]
WIRE ROPE DIA.	12 mm	
MAX. ROPE CAPACITY	39 Mt	[128,0 Ft]
MAX. SPEED LINE	9,2 Mt/Min	[30,2 Ft]
MAX. OIL SUPPLY	60 Lt/Min	[15,85 GPM]

EPH 6700FN



PULLING CAPACITY	6.700 Kgs	[14.770 Lbs]
WORKING PRESSURE	165 Bar	[2,393 Psi]
WIRE ROPE DIA.	12 mm	
MAX. ROPE CAPACITY	39 Mt	[128,0 Ft]
MAX. SPEED LINE	9,2 Mt/Min	[30,2 Ft]
MAX. OIL SUPPLY	60 Lt/Min	[15,85 GPM]



WARNING

Do not use winch to lift support or transport personnel.